



Thank you for purchasing a CAMP EZI quality product.

Please read instructions before use

#### PREPARING FOR USE.

- Unscrew waste tank cap on rear of toilet.
- Add about 3 liters of water into empty waste tank, before adding the chemical (sold separately) and only use recommended amount.
- The rinse tank, remove the inlet cap on top of the rinse tank and add about 5 liters of water and add the chemicals through the inlet, screw inlet cap back on firmly, but not too tight.
- Always wash hands thoroughly with soap and water or disinfectant after handling toilet and chemicals use.
- Open and close the valve blade once with seat and cover closed, this will release excess pressure in holding tank.
- Open valve blade, pump valve once to wet bowl and then pump valve after use to wash the bowl. Then close valve and lid after use.
- To empty the waste tanks, undo the side locks and lift rinse tank off.
- Take the waste tanks to an authorised waste disposal area (or normal toilet) take off the screw cap and tip to empty.

#### STORAGE AND CLEANING.

- Store toilet clean and dry.
- Lubricate seals with a silicon based lubricant to prevent seals drying out.
- Use of regular cleaning products are recommended, however, avoid using abrasive objects.

#### HELPFUL HINTS.

- Avoid long term exposure to direct sunlight.
- Do not lean back on the seat when using the toilet, as this may damage the lid and cause injury.
- Do not use regular toilet paper, as this may cause clogging. Use rapidly dissolving soft toilet paper instead.
- After cleaning always lubricate seals with a silicon based lubricant
- Always wash hands thoroughly with soap and water or disinfectant after cleaning toilet.